



2021 Avon Tyres Sidecar Range

Update: 01-20-2021

Nylon construction (F2 sidecar)

			Hard	Compound					Soft
			A24	A11	A53	A27	A50	A15	A92
6.2/20.0-13	Slick		9210	10595	12240	3623		2921	14227
	<i>Wet/Inter</i>							<i>2921/2921i</i>	<i>14227</i>
7.2/20.0-13	Slick		9116	11916	14443	3814		6538	14254
	<i>Wet/Inter</i>							<i>6538/6538i</i>	<i>14254</i>
8.2/20.0-13	Slick		3832	2260	12241			2555	14140
	<i>Wet/Inter</i>							<i>2555/2555i</i>	<i>14140</i>
9.0/20.0-13	Slick		3425	7210	12765			2553	14143
	<i>Wet/Inter</i>							<i>2553/2553i</i>	<i>14143</i>
10.0/20.0-13	Slick		3856	2545				4134	14251
	<i>Wet/Inter</i>							<i>4134/4134i</i>	<i>14251</i>

Kevlar construction (F1 sidecar)


			Hard	Compound				Soft	
			A24/514	A11	A53	A50	A15		
8.2/20.0-13	Slick				12241		11207	13911	14140
	<i>Wet/Inter</i>							<i>13911/13911i</i>	<i>14140</i>
9.0/20.0-13	Slick			7210	12507			2553	
	<i>Wet/Inter</i>							<i>2553/2553i</i>	<i>14143</i>
10.0/20.0-13	Slick			14763	12509		14196	4134	
	<i>Wet/Inter</i>						<i>14196i</i>	<i>4134/4134i</i>	<i>14251</i>
10.0/21.5-14	Slick			14639	14197			14268	
	<i>Wet/Inter</i>				<i>14197i</i>			<i>14268</i>	
250/570-13	<i>Wet</i>						<i>16041</i>		

Scrubbing in Procedure

Avon Motorsport recommend that a standard scrubbing in procedure be used whenever possible (conditions and regulations allowing). This consists of subjecting the tyres through one gentle heat cycle, gradually loading them up whilst avoiding drifting the sidecar. This should take about three to four laps and the last lap should only be about 80% race speed. A correctly scrubbed in set of tyres will always give more consistent performance over its lifetime than a set that has been used hard from new and will help to avoid problems such as "Cold Graining". It should be noted that it is the loading of tyres that introduces the significant heat, not sliding or wheelspinning.

For any further information please contact:

Harrald Endevelt
 Tel: +31-(0)6 27 19 10 57
 E-mail: info@hp-sidecarparts.eu



X - Denotes the Spec Number